



LRF-6000

LASER RANGE FINDER

The LRF-6000 is a handheld device developed to military standards that allows the monitoring of targets at long distances with the help of its optical system and can measure the distance of these targets using invisible wavelength laser beams.



GENERAL FEATURES

- Range capability: up to 6000m
- Specified performance: 3600m (at visibility 10km, 2,3 x 2,3m nato target, albedo 0,3)
- Laser class: class 1 (eye safe, IEC 60825-1: 2014 ED. 1550nm)
- Magnification: 6x
- Units: meter / yard
- Wireless: bluetooth 4.0
- Digital magnetic compass (azimuth and inclination)
- Weight (without batteries and housing): 550g
- Dimensions (HxWxL): 74mm x 109mm x 147mm
- Nitrogen filled: yes
- Battery: standard CR123A 2x3V
- Battery capacity: >5000 measurements
- Reticle: illuminated optical reticle

ENVIRONMENTAL SPECIFICATIONS

- Tested to MIL-STD-810H
- Operating temperature: -35°C / 50°C
- Storage temperature: -40°C/ 70°C
- Waterproof: 1m, 60 minutes
- Vibration: 3g / 30min / xyz

DIGITAL MAGNETIC COMPASS

- Heading range: 360°
- Heading accuracy / resolution: 2° RMS / 0,1°
- Tilt range: 90°
- Tilt accuracy / resolution: 1° RMS / 0,1°

TECHNICAL FEATURES

- Time per measurement: 1,8s (full performance)
- Field of view (FOV): 6°
- Dioptric setting: +4 to -4 diopters
- Lens coating: anti-reflective coating
- Exit pupil diameter: 5mm
- Measurement accuracy: ±1m
- Minimum measurement distance: 20m
- Azimuth accuracy: 2° RMS
- Inclination accuracy: 1° RMS
- Laser type: diode laser
- Laser wavelength: 1550nm
- Laser divergence: 1,25mrad

DATA INTERFACE

- Standard interface type: RS232
- Wireless: bluetooth 4.0
- Interactive mobile interface for bluetooth

DISPLAY

- Number of pixels: 304x256 pixel
- Pixel pitch: 12µm x 12µm
- OLED-on-CMOS technology (red monochrome)

ACCESSORIES

- Shock absorber rubber cover
- User's manual
- Carry bag
- Lens cleaning tissue
- Tripod (optional)



www.gempanet.com.tr info@gempanet.com.tr +90 312 426 14 80

Dicle Caddesi, Akarçay Sk. No:3, 06800 Beysukent-Çankaya/ANKARA